Complex systems

https://doi.org/10.1038/s43588-026-01064-z

Steering complex rhythms

Fan Jin

Check for updates

A recent study reports a property-first computational strategy, identifying coordinated parameter changes that can tune several features of a complex oscillator at the same time.

A heartbeat can speed up while its amplitude changes little, and a circadian clock can shift its timing while keeping protein levels within a safe range. Such selective adjustments are easy to describe but hard to design, because the properties of an oscillator are entangled through the parameters that generate them. This is a fundamental problem across many areas of computational science. Oscillators are described by measurable features — period, amplitude, peak, trough and relative phase — while their dynamics are controlled by reaction rates, coupling strengths, circuit components or environmental conditions. Altering one parameter usually moves several features at once. Classical control often aims to drive the full state of a system along a prescribed trajectory; here, by contrast, the objective is to make a smaller set of observable properties reach specified values. This remains difficult because the selected properties are coupled through the same underlying parameters, even when other details of the waveform are allowed to vary. In this issue, Cai and colleagues present a mathematical and computational framework for deciding when several oscillatory properties can be specified together and for finding the coordinated parameter changes that realize them[1].

Biological oscillators have long served as test beds. The repressilator showed that a synthetic gene network could generate sustained rhythms[2]. Later studies linked feedback architecture to tunability[3] and redesigned circuits to adjust amplitude and period more independently[4,5]. Yet many such strategies rely on scanning large parameter grids or on redesigning a particular system. Both become less effective as the number of tunable parameters and requested properties grows.

The authors bring structure to this inverse problem by distinguishing three levels of 'modulatability': whether a target point can be




Fig. 1 | From rhythmic properties to coordinated parameter changes. a, Period, amplitude, extrema and relative phase define a space of target behaviors. **b**,**c**, Rather than scanning parameter combinations, the framework follows a selected path through this property space and computes the corresponding path through adjustable parameters. Adapted from ref. 1, Springer Nature America, Inc.

reached, whether all targets in a region can be reached, and whether a continuous route between two target states has a corresponding continuous route through parameter space. Under stated non-degeneracy conditions, they show that a locally unique solution requires the number of independent adjustable parameters to equal the number of target properties. Thus, two independently specified features generally call for two independent handles, and three features call for three. The qualification matters: the result is local and depends on regularity, rather than promising a feasible solution for every target.

Network simulations then probe this rule in higher dimensions. Across gene-regulatory and neuronal networks with varied sizes, topologies and target thresholds, successful modulation generally appears when the number of perturbed edges reaches the number of target amplitudes. These tests support the design rule numerically, but do not turn the local theorem into a global guarantee.

As Fig. 1 illustrates, the computational scheme starts by describing a rhythm through measurable properties such as period and amplitude. It then selects a route from the current rhythm to the desired target in this property space and calculates the coordinated changes in adjustable parameters needed to follow that route. A change of time coordinates, a compact representation of the waveform and an iterative solver carry out this calculation. The practical idea is to specify the destination first and then determine how the controls must move together.

The authors test the framework on networks of coupled gene-regulatory and neuronal oscillators, several biological circuit models and an electronic analogue of the repressilator. The electronic circuit is a particularly informative test because it links model-based calculations to measurements: voltage traces allow the framework first to infer component values from selected oscillatory properties and then to tune the physical circuit. The framework also handles a derived observable rather than a model variable directly, illustrated by the total abundance of a circadian protein across cellular compartments.

These examples support the breadth of the formulation, although most biological demonstrations remain model based. The main advance is therefore not a universal recipe for manipulating any living oscillator. It is a common language and a constructive route for problems that were often treated separately: existence, local uniqueness, parameter inference and multi-property tuning. Benchmarks against standard sampling and optimization methods show why avoiding exhaustive parameter search can help as the number of targets grows, while also making clear that the cost still rises with model size, waveform resolution and numerical stiffness.

Important limitations point to the next steps. The method assumes a mechanistic model and accessible parameters, whereas experimental systems are often only partly known and only a few controls can be changed safely. A path may also end at a bifurcation, cross an unstable regime or fail because the initial and target rhythms lie in disconnected feasible regions. Property matching does not by itself provide uncertainty intervals for inferred parameters. Combining the framework with statistical inference, experimental feedback and automated detection of path failure would make it more useful in noisy settings.

Most oscillators will not yield to a single control parameter. Their useful behaviors are more likely to be reached by coordinated changes, and those changes have a geometry. The framework of Cai and colleagues makes that geometry calculable, turning reachability, required controls and routes between rhythms into questions that can be posed before an experiment is attempted.

Fan Jin
State Key Laboratory of Quantitative Synthetic Biology, Shenzhen Institutes of Advanced Technology, Chinese Academy of Sciences, Shenzhen, China.
e-mail: fan.jin@siat.ac.cn

Published online: 09 October 2026

References

1. Cai, Y., Zhong, Z., Zhang, Z., Qin, B.-W. & Lin, W. *Nat. Comput. Sci.* https://doi.org/10.1038/s43588-026-01050-5 (2026).
2. Elowitz, M. B. & Leibler, S. *Nature* **403**, 335–338 (2000).
3. Tsai, T. Y.-C. et al. *Science* **321**, 126–129 (2008).
4. Tomazou, M. et al. *Cell Syst.* **6**, 508–520.e5 (2018).
5. Zhang, F. et al. *Commun. Biol.* **5**, 23 (2022).

Competing interests

The author declares no competing interests.